

# Water Leak Detector

## WLD Panel

PCD20 WLD 2Z / PCD20 WLD 4Z

PCD20 WLD 6Z / PCD20 WLD 8Z



ANISO9001: 2008COMPANY-

Water Leak Detector System comprises of a robust Control panel and sensor cable accessories for detection.

Physical environmental threats that plague Infrastructure Maintenance Managers besides security attacks and connectivity failures are temperature, humidity, water leak, rodent menace, human error etc. Such threats can damage equipment, slow performance and force hardware to shutdown. Lost revenues due to unavailable server based applications such as e-Commerce site or customer service centers are not insurable and also ruins the value of an organization. Safeguarding against such crisis is the need of the hour.

Water Leak Detector System offers an effective Environment Monitoring solution for problems associated with water leak in server, data and computer rooms. The ultra compact device with its intelligent sensor cables monitor, detect and communicate the presence of liquid via audio - visual alarms to the server administrators. Its user friendly software offers the technicians unsurpassed flexibility in navigation and damage control.



### FEATURES

#### Control Panel

- The Controller has in built software to sense, receive and recognize the signals sent by the sensor cables.
- In the event of any abnormal condition or malfunction it activates an alarm that has to be acknowledged physically and reset.
- In built connectors are provided for interfacing the hooters and RS485. Has optional 2 to 8 zones (areas) adaptability.
- Software for monitoring and report generation.
- Events logging.
- It needs a power connection and comes equipped with a 3-pin power supply cord.

### SPECIFICATION

#### Control panel

Configuration	: Control Panel with optional (2 to 8) zones
Operating Voltage	: 230V AC 50 Hz
Dimension	: 305 x 225 x 85 mm.
Weight	: 2.5 Kgs
Mounting	: Wall

### DISPLAY

- 4 x 20 LCD for displaying status of all water leakage sensors, Door status.
- LED Display status for all zones.

### SENSOR CABLES

- Reliably senses any conductive fluid.
- Non conductive and abrasion resistant polymers increase the strength of the cables.
- Pressure on the cables will not create any false alarm.
- Detects fluid along the entire length.
- Flexible and easy to maintain.

#### Sensor Cables

Leader cable	: 5 mts
Sensor Cable length	: 10, 15, 20 and 25 mts.

☎ 022 41205036 / 022 25003210 | CEO: Joseph Rozario: 9930533861

✉ sales@pcdfire.co.in info@linovate.in 🌐 www.pcdfire.co.in

**Head Office** - Ground Floor, C-15 Kailash Esplanade, L.B.S. Marg, Ghatkopar (w), Mumbai 400086

**Works** - Ghatkopar Industrial Estate, B/h R-City Mall, L.B.S. Marg, Ghatkopar (w), Mumbai 400086