

Fire Alarm Accessories

Firemans Telephone

Model: FTH-01/02



ANISO9001: 2008COMPANY-

FEATURES

- Duplex communications.
- Available in 2 versions
- Break glass with Handset behind door closed door.
- Or wall socket with status indication.
- Simple operation just lift handset to talk
- Cable saving 4 pair cat 5/6 network cable.
- Control Panel operation on 24v DC
- Micro processor based design with addressable model
- Conference calls for up to 5 stations.
- Sleek counter sunk talk back stations.

MODEL: FTH-01

Telephone handset Module with Break Glass
MS Cabinet Size: 160 x 360 x 90 mm. Flush Mounted



SPECIFICATIONS

24v DC UPS from Panel.
2 wire data communications.
Pulsing communications LED (Green).
Yellow call detected ACK LED.
Red LED to indicate call registered
Addressable Module with 5 bit Address switch.
Microprocessor with embedded firmware SMT technology.
Loop Length 300m Cat5 4 pair cable.
Size: 90 x 118 x 5 mm

Hand set only with RJ-11 Telephone Plug.
Complete with Duplex Voice Amplifier ear piece and microphone also available with push to Talk Push Switch - Option for use with FTH-02



Model: FHS-02



Floor Module zone 16




4 pair CAT5/6 network Cable loop for modules on 1st to 16th Floor

Floor Module Zone 1



Talk back Control Panel



230 v AC

Model: ANL-16-FTC.1
16 Zone 1 Loop Panel

Single Line wiring drawing

Loop length Maximum 300 mtr Cat 6 4 pair cable.
or Maximum 800 mtr around cable length 1.5sq. mm. per Loop 16 modules Max. Multiple loop panels available for large installations.

☎ 022 41205036 / 022 25003210 | CEO: Joseph Rozario: 9930533861

✉ sales@pcdfire.co.in info@linovate.in 🌐 www.pcdfire.co.in

Head Office - Ground Floor, C-15 Kailash Esplanade, L.B.S. Marg, Ghatkopar (w), Mumbai 400086

Works - Ghatkopar Industrial Estate, B/h R-City Mall, L.B.S. Marg, Ghatkopar (w), Mumbai 400086