

Fire Alarm Accessories

Illuminated Signs

(Warning Flashing Signs)

Model: 4TS-90-FR-M2.1



ANISO9001: 2008COMPANY-

SPECIFICATIONS

Supply Voltage : 24v. DC.

Characters Engraved : On acrylic.

Character color : Red

Current consumption : 120 mA.

Dimensions : W 150 x H 230 x D 80 mm

Sign Illumination : Multi Red LED's

Construction : Edge lit acrylic sheet

Flasher : High watt white LED's

Hooter : 86 dB. Multi tone.

MODEL

4TS-90-FR-M1.1

Cable Entry : Top

Mounting : Wall MS Back Box provided.

Color : Red



SPECIFICATIONS

Supply Voltage : 24v. DC.

Characters Engraved : on Acrylic.

Character color : Red

Current consumption : 120 mA.

Dimensions : W 150 x H 230 x D 80 mm

Sign Illumination : Multi Red LED's

Construction : edge lit Acrylic sheet

Flasher : High Watt White LED's

Hooter : 86 dB. Multi tone.

MODEL

4TS-90-FR-M2.1

Cable Entry : Top

Mounting : Wall MS Back Box provided.

Color : Red



Messages Available : "EVACUATE", "DO NOT ENTER GAS RELEASED" Also User defined messages can be provided to order.

WWW.PCDFIRE.COM - Please Visit Our Website for Other Product Information

022 41205036 | 022 250003210 | 9930533861 | 9920520573 | 9987665570

sales@pcdfire.com | joseph@pcdfire.com | crispin@pcdfire.com

Head Office: Office No E1-110, Kailash Esplanade, LBS Marg, Ghatkopar West, Mumbai – 400 086
Works: Ghatkopar Industrial Estate, B/h R-City Mall, LBS Marg, Ghatkopar West, Mumbai – 400 086

LINOVATE TECHNOLOGIES : Authorized Channel Partners For Pan India & OEM for PCD make Fire Alarm Systems

Pg 1/1